


1-1 システムマルチ室外ユニット一覧..... 1-1-1

1-2 システムマルチ室内ユニット一覧..... 1-2-1

■既設配管対応 ハイグレード UXP5R

相当馬力	品番		冷房能力 (kW)	暖房能力 (kW)	室内ユニット 最多接続 台数 (台)	外観			
8	CU-P224UXPR5R	標準単独ユニット	22.4	25.0	20	①			
10	CU-P280UXPR5R		28.0	31.5	25				
12	CU-P335UXPR5R		33.5	37.5	30				
14	CU-P400UXPR5R		40.0	45.0	36				
16	CU-P450UXPR5R		45.0	50.0	40				
	組み合わせ品番	構成ユニット							
18	PA-P500UXPR5R	CU-P224UXPR5R CU-P280UXPR5R	50.0	56.0	45	③			
20	PA-P560UXPR5R	CU-P224UXPR5R CU-P335UXPR5R	56.0	63.0	50				
22	PA-P615UXPR5R	CU-P280UXPR5R CU-P335UXPR5R	61.5	69.0	55				
24	PA-P670UXPR5R	CU-P335UXPR5R CU-P335UXPR5R	67.0	77.5	60				
26	PA-P730UXPR5R	CU-P335UXPR5R CU-P400UXPR5R	73.0	82.5	64	④			
28	PA-P775UXPR5R	CU-P335UXPR5R CU-P450UXPR5R	77.5	90.0					
30	PA-P850UXPR5R	CU-P400UXPR5R CU-P450UXPR5R	85.0	95.0		⑤			
32	PA-P900UXPR5R	CU-P450UXPR5R CU-P450UXPR5R	90.0	100					
34	PA-P950UXPR5R	CU-P280UXPR5R CU-P335UXPR5R CU-P335UXPR5R	95.0	106		⑥			
36	PA-P1000UXPR5	CU-P335UXPR5R CU-P335UXPR5R CU-P335UXPR5R	100	112					
38	PA-P1060UXPR5	CU-P335UXPR5R CU-P335UXPR5R CU-P400UXPR5R	106	118		⑦			
40	PA-P1120UXPR5R	CU-P335UXPR5R CU-P335UXPR5R CU-P450UXPR5R	112	125					
42	PA-P1180UXPR5R	CU-P335UXPR5R CU-P400UXPR5R CU-P450UXPR5R	118	132				⑧	
44	PA-P1220UXPR5R	CU-P335UXPR5R CU-P450UXPR5R CU-P450UXPR5R	122	140					
46	PA-P1280UXPR5R	CU-P400UXPR5R CU-P450UXPR5R CU-P450UXPR5R	128	145		⑨			
48	PA-P1360UXPR5R	CU-P450UXPR5R CU-P450UXPR5R CU-P450UXPR5R	136	150					

■既設配管対応 ハイグレード（高 COP タイプ）UXPR5YR

相当 馬力	品番		冷房 能力 (kW)	暖房 能力 (kW)	室内 ユニット 最多接続 台数 (台)	外観	
6	CU-P160UXPR5YR	標準単独ユニット	16.0	18.0	—		
8	CU-P224UXPR5YR		22.4	25.0	20		
10	CU-P280UXPR5YR		28.0	31.5	25		
	組み合わせ品番	構成ユニット					
12	PA-P335UXPR5YR	CU-P160UXPR5YR CU-P160UXPR5YR	33.5	37.5	30		
14	PA-P400UXPR5YR	CU-P160UXPR5YR CU-P224UXPR5YR	40.0	45.0	36		
16	PA-P450UXPR5YR	CU-P224UXPR5YR CU-P224UXPR5YR	45.0	50.0	40		
18	PA-P500UXPR5YR	CU-P224UXPR5YR CU-P280UXPR5YR	50.0	56.0	45		
20	PA-P560UXPR5YR	CU-P160UXPR5YR CU-P160UXPR5YR CU-P224UXPR5YR	56.0	63.0	50		
22	PA-P615UXPR5YR	CU-P160UXPR5YR CU-P224UXPR5YR CU-P224UXPR5YR	61.5	69.0	55		
24	PA-P670UXPR5YR	CU-P224UXPR5YR CU-P224UXPR5YR CU-P224UXPR5YR	67.0	77.5	60		
26	PA-P730UXPR5YR	CU-P224UXPR5YR CU-P224UXPR5YR CU-P280UXPR5YR	73.0	82.5	64		
28	PA-P775UXPR5YR	CU-P160UXPR5YR CU-P160UXPR5YR CU-P224UXPR5YR CU-P224UXPR5YR	77.5	90.0			
30	PA-P850UXPR5YR	CU-P160UXPR5YR CU-P224UXPR5YR CU-P224UXPR5YR CU-P224UXPR5YR	85.0	95.0			
32	PA-P900UXPR5YR	CU-P224UXPR5YR CU-P224UXPR5YR CU-P224UXPR5YR CU-P224UXPR5YR	90.0	100			
34	PA-P950UXPR5YR	CU-P224UXPR5YR CU-P224UXPR5YR CU-P224UXPR5YR CU-P280UXPR5YR	95.0	106			
36	PA-P1000UXPR5YR	CU-P224UXPR5YR CU-P224UXPR5YR CU-P280UXPR5YR CU-P280UXPR5YR	100	112			

■既設配管対応 高効率 UXR5

相当馬力	品番		冷房能力 (kW)	暖房能力 (kW)	室内ユニット 最多接続 台数 (台)	外観		
8	CU-P224UXR5	標準単独ユニット	22.4	25.0	13	①		
10	CU-P280UXR5		28.0	31.5	16			
12	CU-P335UXR5		33.5	37.5	19			
14	CU-P400UXR5		40.0	45.0	23			
16	CU-P450UXR5		45.0	50.0	26			
	組み合わせ品番	構成ユニット						
18	PA-P500UXR5	CU-P224UXR5 CU-P280UXR5	50.0	56.0	29	③		
20	PA-P560UXR5	CU-P280UXR5 CU-P280UXR5	56.0	63.0	33			
22	PA-P615UXR5	CU-P280UXR5 CU-P335UXR5	61.5	69.0	36			
24	PA-P670UXR5	CU-P335UXR5 CU-P335UXR5	67.0	77.5	39			
26	PA-P730UXR5	CU-P335UXR5 CU-P400UXR5	73.0	82.5	43			
28	PA-P775UXR5	CU-P335UXR5 CU-P450UXR5	77.5	90.0	45	④	 	
30	PA-P850UXR5	CU-P400UXR5 CU-P450UXR5	85.0	95.0	50			
32	PA-P900UXR5	CU-P450UXR5 CU-P450UXR5	90.0	100	53	⑤		
34	PA-P950UXR5	CU-P280UXR5 CU-P335UXR5 CU-P335UXR5	95.0	106	56			
36	PA-P1000UXR5	CU-P335UXR5 CU-P335UXR5 CU-P335UXR5	100	112	59	⑥		
38	PA-P1060UXR5	CU-P335UXR5 CU-P335UXR5 CU-P400UXR5	106	118	62			
40	PA-P1120UXR5	CU-P335UXR5 CU-P335UXR5 CU-P450UXR5	112	125	64	⑦		
42	PA-P1180UXR5	CU-P335UXR5 CU-P400UXR5 CU-P450UXR5	118	132				
44	PA-P1220UXR5	CU-P335UXR5 CU-P450UXR5 CU-P450UXR5	122	140		⑧		
46	PA-P1280UXR5	CU-P400UXR5 CU-P450UXR5 CU-P450UXR5	128	145				
48	PA-P1360UXR5	CU-P450UXR5 CU-P450UXR5 CU-P450UXR5	136	150		⑨		
50	PA-P1400UXR5	CU-P280UXR5 CU-P335UXR5 CU-P335UXR5 CU-P450UXR5	140	156				
52	PA-P1450UXR5	CU-P335UXR5 CU-P335UXR5 CU-P335UXR5 CU-P450UXR5	145	160		⑩		
54	PA-P1500UXR5	CU-P335UXR5 CU-P335UXR5 CU-P400UXR5 CU-P450UXR5	150	165				
							⑪	

■新設・既設配管兼用 寒冷地向け UXKR5

相当馬力	品番		冷房能力 (kW)	暖房能力 (kW)	室内ユニット 最多接続台数 (台)	外観	
8	CU-P224UXKR5	標準単独ユニット	22.4	25.0	20		① ②
10	CU-P280UXKR5		28.0	31.5	25		
12	CU-P355UXKR5		33.5	37.5	30		
	組み合わせ品番	構成ユニット					
16	PA-P450UXKR5	CU-P224UXKR5 CU-P224UXKR5	45.0	50.0	40		③
18	PA-P500UXKR5	CU-P280UXKR5 CU-P224UXKR5	50.0	56.0	45		
20	PA-P560UXKR5	CU-P280UXKR5 CU-P280UXKR5	56.0	63.0	50		
22	PA-P615UXKR5	CU-P355UXKR5 CU-P280UXKR5	61.5	69.0	55		④
24	PA-P670UXKR5	CU-P355UXKR5 CU-P355UXKR5	67.0	77.5	60		
26	PA-P730UXKR5	CU-P280UXKR5 CU-P224UXKR5 CU-P224UXKR5	73.0	82.5	64		⑤
28	PA-P755UXKR5	CU-P280UXKR5 CU-P280UXKR5 CU-P224UXKR5	77.5	90.0			
30	PA-P850UXKR5	CU-P280UXKR5 CU-P280UXKR5 CU-P280UXKR5	85.0	95.5			⑥
32	PA-P900UXKR5	CU-P355UXKR5 CU-P280UXKR5 CU-P280UXKR5	90.0	100			
34	PA-P950UXKR5	CU-P355UXKR5 CU-P355UXKR5 CU-P280UXKR5	95.0	106			⑦
36	PA-P1000UXKR5	CU-P355UXKR5 CU-P355UXKR5 CU-P355UXKR5	100	112			
							⑧
							⑨

■ mini マルチ UL4R

相当 馬力	品番		冷房 能力 (kW)	暖房 能力 (kW)	室内 ユニット 最多接続 台数 (台)	外観
4	CU-P112UL4R	標準単独ユニット	11.2	12.5	2～6	
5	CU-P140UL4R		14.0	16.0	2～8	
6	CU-P160UL4R		16.0	18.0	2～9	

■ オフィス・店舗用マルチエアコン ULR5R

相当 馬力	品番		冷房 能力 (kW)	暖房 能力 (kW)	室内 ユニット 最多接続 台数 (台)	外観
8	CU-P224ULR5R	標準単独ユニット	20.0	22.4	1～13	
10	CU-P280ULR5R		25.0	28.0	1～16	

形式	相当馬力	冷房能力 (kW)	暖房能力 (kW)	4方向天井カセット形	4方向天井カセット形	4方向天井カセット形	4方向天井カセット形
							
22形	0.8	2.2	2.5				
28形	1.0	2.8	3.2	CS-EP28U7U	CS-P28U5U		
36形	1.3	3.6	4.2	CS-EP36U7U	CS-P36U5U		
45形	1.6	4.5	5.0	CS-EP45U7U	CS-P45U5U		
56形	2.0	5.6	6.3	CS-EP56U7U	CS-P56U5U	CS-EP56U7DU	
71形	2.5	7.1	8.0	CS-EP71U7U	CS-P71U5U	CS-EP71U7DU	
80形	3.0	8.0	9.0	CS-EP80U7U	CS-P80U5U	CS-EP80U7DU	CS-P80U4DU
90形	3.2	9.0	10.0	CS-EP90U7U	CS-P90U5U	CS-EP90U7DU	CS-P90U4DU
112形	4.0	11.2	12.5	CS-EP112U7U	CS-P112U5U	CS-EP112U7DU	CS-P112U4DU
140形	5.0	14.0	16.0	CS-EP140U7U	CS-P140U5U	CS-EP140U7DU	CS-P140U4DU
160形	6.0	16.0	18.0	CS-EP160U7U	CS-P160U5U	CS-EP160U7DU	CS-P160U4DU
224形	8.0	22.4	25.0				
280形	10.0	28.0	31.5				

形式	相当馬力	冷房能力 (kW)	暖房能力 (kW)	2方向天井カセット形	1方向天井カセットスリム形	1方向天井カセット形	高天井用1方向カセット形
							
22形	0.8	2.2	2.5	CS-EP22L7U	CS-EP22DS7(M)U	CS-P22DM5U	
28形	1.0	2.8	3.2	CS-EP28L7U	CS-EP28DS7(M)U	CS-P28DM5U	CS-P28D3U
36形	1.3	3.6	4.2	CS-EP36L7U		CS-P36DM5U	CS-P36D3U
45形	1.6	4.5	5.0	CS-EP45L7U			CS-P45D3U
56形	2.0	5.6	6.3	CS-EP56L7U			CS-P56D3U
71形	2.5	7.1	8.0	CS-EP71L7U			CS-P71D3U
80形	3.0	8.0	9.0	CS-EP80L7U			CS-P80D3U
90形	3.2	9.0	10.0	CS-EP90L7U			
112形	4.0	11.2	12.5	CS-EP112L7U			
140形	5.0	14.0	16.0	CS-EP140L7U			
160形	6.0	16.0	18.0	CS-EP160L7U			
224形	8.0	22.4	25.0				
280形	10.0	28.0	31.5				


形式	相当馬力	冷房能力 (kW)	暖房能力 (kW)	天井ビルトイン カセット形	ビルトイン オールダクト形	天井埋込形	天井吊形
							
22 形	0.8	2.2	2.5	CS-P22F5U			
28 形	1.0	2.8	3.2	CS-P28F5U	CS-P28FE5U(L)		
36 形	1.3	3.6	4.2	CS-P36F5U	CS-P36FE5U(L)		CS-EP36T7U
45 形	1.6	4.5	5.0	CS-P45F5U	CS-P45FE5U(L)		CS-EP45T7U
56 形	2.0	5.6	6.3	CS-P56F5U	CS-P56FE5U(L)		CS-EP56T7U
71 形	2.5	7.1	8.0	CS-P71F5U	CS-P71FE5U		CS-EP71T7U
80 形	3.0	8.0	9.0	CS-P80F5U	CS-P80FE5U		CS-EP80T7U
90 形	3.2	9.0	10.0	CS-P90F5U	CS-P90FE5U		CS-EP90T7U
112 形	4.0	11.2	12.5	CS-P112F5U	CS-P112FE5U		CS-EP112T7U
140 形	5.0	14.0	16.0	CS-P140F5U	CS-P140FE5U		CS-EP140T7U
160 形	6.0	16.0	18.0	CS-P160F5U	CS-P160FE5U		CS-EP160T7U
224 形	8.0	22.4	25.0			CS-P224E3U	
280 形	10.0	28.0	31.5			CS-P280E3U	

形式	相当馬力	冷房能力 (kW)	暖房能力 (kW)	壁掛形	床置ダクト形	ペリメーター用 床置形	ペリメーター用 床置埋込形
							
22 形	0.8	2.2	2.5				
28 形	1.0	2.8	3.2	CS-P28K5U		CS-P28P5U	CS-P28PM5U
36 形	1.3	3.6	4.2	CS-P36K5U		CS-P36P5U	CS-P36PM5U
45 形	1.6	4.5	5.0	CS-P45K5U		CS-P45P5U	CS-P45PM5U
56 形	2.0	5.6	6.3	CS-P56K5U		CS-P56P5U	CS-P56PM5U
71 形	2.5	7.1	8.0	CS-P71K5U		CS-P71P5U	CS-P71PM5U
80 形	3.0	8.0	9.0			CS-P80P5U	CS-P80PM5U
90 形	3.2	9.0	10.0				
112 形	4.0	11.2	12.5				
140 形	5.0	14.0	16.0				
160 形	6.0	16.0	18.0				
224 形	8.0	22.4	25.0		CS-P224BD5U		
280 形	10.0	28.0	31.5		CS-P280BD5U		

形式	相当 馬力	冷房 能力 (kW)	暖房 能力 (kW)	天吊形厨房用 エアコン
				
80 形	3.0	8.0	9.0	CS-P80V5U
112 形	4.0	11.2	12.5	CS-P112V5U
140 形	5.0	14.0	16.0	CS-P140V5U

形式	相当 馬力	冷房 能力 (kW)	暖房 能力 (kW)	壁ビルトイン形
				
140 形	5.0	14.0	14.0	CS-P140W(N)4U
224 形	8.0	22.4	22.4	CS-P224W(N)4U
280 形	10.0	28.0	28.0	CS-P280W(N)4UN

形式	相当 馬力	冷房 能力 (kW)	暖房 能力 (kW)	床置形 ハイフレッシュ
				
200 形	10.0	28.0	26.7	CS-P200XW4U

形式	相当 馬力	冷房 能力 (kW)	暖房 能力 (kW)	直膨コイル付 外気処理ユニット
				
50 形	3.6	5.51	6.69	CS-P50X3U
75 形	4.5	7.95	9.73	CS-P75X3U
75 形	5.6	9.87	11.32	CS-P100X3U

形式	相当 馬力	冷房 能力 (kW)	暖房 能力 (kW)	天井埋込形 ハイフレッシュ
				
110 形	5.0	14.0	13.2	CS-P110XE3U
170 形	8.0	22.4	21.2	CS-EP170XE7U
210 形	10.0	28.0	26.5	CS-EP210XE7U

形式	相当 馬力	冷房 能力 (kW)	暖房 能力 (kW)	クリーン PAC	
				吸込一体形	壁下吸込形
					
45 形	1.6	4.5	5.0	CS-P45CK4U(5,6)	CS-P45CD4U(5,6)
56 形	2.0	5.6	6.3	CS-P56CK4U(5,6)	CS-P56CD4U(5,6)
71 形	2.5	7.1	8.0	CS-P71CK4U(5,6)	CS-P71CD4U(5,6)

形式	相当 馬力	冷房 能力 (kW)	暖房 能力 (kW)	設備用	
				床置プレナム形	床置ダクト形
					
560 形	20	56.0	63.0	CS-P560AS4(5,6)	CS-P560ASD4(5,6)
850 形	30	85.0	95.0		CS-P850ASD4
1120 形	40	112	125		CS-P1120ASD4
1400 形	50	140	155		CS-P1400ASD4
1600 形	60	160	190		CS-P1600ASD4